



HUB MOUNT



BOLT MOUNT



SIMPLEX MOUNT



CLAMP MOUNT

ALUMINUM ARM ASSEMBLIES

All Sequoia Lighting roadway arm assemblies mount to a variety of aluminum poles. Each arm assembly is available to accommodate one or two luminaires depending on mounting configuration. Brackets come complete with locking set depending on application and are finished to match pole. Arms cataloged are fabricated from aluminum and are designed for use on aluminum poles.

All aluminum arm assemblies are polished with fine grain aluminum oxide clothes, resulting in a high quality circumferential satin brush finish. Custom paint colors and special finishes are also available.

*If required roadway arm is not shown please consult factory.

SEQUOIA LIGHTING
CORPORATION

MANUFACTURERS OF QUALITY LIGHTING PRODUCTS

13644 George Blvd, Suite 1, Victorville, CA, 92394 (760) 246-5213 FAX (760) 246-5294 www.sequoialighting.com

Roadway - 1PA-Series

STRUCTURE DATA										
Catalog Number	Mounting Height (ft)	Gross weight (Lbs)	Pole Shaft Data				Arm	Base Plate Data		Anchor Bolt Data
			Base O.D. (in)	Top O.D. (in)	Wall Thk. (in)	Shaft Length (ft)		A Length (ft)	Bolt Circle Range (in)	
SL-20-50B-104XP	20	74	5.0	3.0	.156	17.66	4	7.5-9.5	9.25	0.75 x 15 x 3
SL-20-50V-104XP		84	5.0	3.0	.188	17.66	4	7.5-9.5	9.25	0.75 x 15 x 3
SL-20-60B-104XP		92	6.0	4.0	.156	17.66	4	8.75-10.25	10.25	0.75 x 25 x 4
SL-20-60V-104XP		103	6.0	4.0	.188	17.66	4	8.75-10.25	10.25	0.75 x 25 x 4
SL-20-50B-106XP		77	5.0	3.0	.156	17.66	6	7.5-9.5	9.25	0.75 x 15 x 3
SL-20-50V-106XP		87	5.0	3.0	.188	17.66	6	7.5-9.5	9.25	0.75 x 15 x 3
SL-20-60B-106XP		95	6.0	4.0	.156	17.66	6	8.75-10.25	10.25	0.75 x 25 x 4
SL-20-60B-108XP		97	6.0	4.0	.156	17.66	8	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-60B-104XP		25	106	6.0	4.0	.156	22.66	4	8.75-10.25	10.25
SL-25-60V-104XP	118		6.0	4.0	.188	22.66	4	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-70B-104XP	133		7.0	4.0	.156	22.66	4	9.875-11.25	10.63	1 x 36 x 4
SL-25-60B-106XP	109		6.0	4.0	.156	22.66	6	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-60V-106XP	121		6.0	4.0	.188	22.66	6	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-70B-106XP	136		7.0	4.0	.156	22.66	6	9.875-11.25	10.63	1 x 36 x 4
SL-25-60B-108XP	111		6.0	4.0	.156	22.66	8	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-60V-108XP	123		6.0	4.0	.188	22.66	8	8.75-10.25	10.25	0.75 x 25 x 4
SL-25-70B-108XP	138		7.0	4.0	.156	22.66	8	9.875-11.25	10.63	1 x 36 x 4
SL-30-70B-104XP	30	157	7.0	4.0	.156	27.66	4	9.875-11.25	10.63	1 x 36 x 4
SL-30-80B-104XP		161	8.0	4.5	.156	27.66	4	11-12.125	11.63	1 x 36 x 4
SL-30-80V-104XP		184	8.0	4.5	.188	27.66	4	11-12.125	11.63	1 x 36 x 4
SL-30-70B-106XP		160	7.0	4.0	.156	27.66	6	9.875-11.25	10.63	1 x 36 x 4
SL-30-80B-106XP		164	8.0	4.5	.156	27.66	6	11-12.125	11.625	1 x 36 x 4
SL-30-70B-108XP		162	7.0	4.0	.156	27.66	8	9.875-11.25	10.625	1 x 36 x 4
SL-30-80B-108XP		166	8.0	4.5	.156	27.66	8	11-12.125	11.625	1 x 36 x 4
SL-35-80B-104XP		35	188	8.0	4.5	.156	32.66	4	11-12.125	11.625
SL-35-80V-104XP	215		8.0	4.5	.188	32.66	4	11-12.125	11.625	1 x 36 x 4
SL-35-80H-104XP	264		8.0	4.5	.250	32.66	4	11-12.125	11.625	1 x 36 x 4
SL-35-80B-106XP	191		8.0	4.5	.156	32.66	6	11-12.125	11.625	1 x 36 x 4
SL-35-80V-106XP	218		8.0	4.5	.188	32.66	6	11-12.125	11.625	1 x 36 x 4
SL-35-80H-106XP	267		8.0	4.5	.250	32.66	6	11-12.125	11.625	1 x 36 x 4
SL-35-80B-108XP	193		8.0	4.5	.156	32.66	8	11-12.125	11.625	1 x 36 x 4
SL-35-80V-108XP	220		8.0	4.5	.188	32.66	8	11-12.125	11.625	1 x 36 x 4
SL-35-80H-108XP	269		8.0	4.5	.250	32.66	8	11-12.125	11.625	1 x 36 x 4
SL-39-80V-104XP	39	237	8.0	4.5	.188	36.66	4	11-12.125	11.625	1 x 36 x 4
SL-39-80H-104XP		299	8.0	4.5	.250	36.66	4	11-12.125	11.625	1 x 36 x 4
SL-39-80V-106XP		240	8.0	4.5	.188	36.66	6	11-12.125	11.625	1 x 36 x 4
SL-39-80H-106XP		302	8.0	4.5	.250	36.66	6	11-12.125	11.625	1 x 36 x 4
SL-39-80V-108XP		242	8.0	4.5	.188	36.66	8	11-12.125	11.625	1 x 36 x 4
SL-39-80H-108XP		304	8.0	4.5	.250	36.66	8	11-12.125	11.625	1 x 36 x 4

Replace "X" with the following:

H - Hub-mounted

B - Bolt-mounted

S - Simplex-mounted

C - Clamp-mounted